



- 1 Male suspension link.
- 2 360° hydraulic rotation.
- 3 Body in high tensile steel.  
2 inner body horizontal cylinders .
- 4 Shells in wear resistant steel.  
2 sizes of shells according the required capacity.  
Easy filling with overflow draining.
- 5 Vertical shells opening to the ground.
- 6 Kinematic designed to clear off the ground.


**Size**

**L**

**A**
**B**
**C**
**D**
**E**


	t	Size	L mm	liter	kg	A mm	B mm	C mm	D mm	E mm	bar	liter/mn	bar	liter/mn	t	t
BA 2VH	20	PP	1700	2150	2500	1743	1514	2442	2547	350	350	125/250	250	20/30	27/37	36/53
BA 2VH	20	PP	1800	2300	2548	1743	1514	2442	2547	350	350	125/250	250	20/30	27/37	36/53
BA 2VH	20	PP	1900	2450	2596	1743	1514	2442	2547	350	350	125/250	250	20/30	27/37	36/53
BA 2VH	20	PP	2000	2600	2646	1743	1514	2442	2547	350	350	125/250	250	20/30	27/37	36/53
BA 2VH	20	PP	2100	2750	2694	1743	1514	2442	2547	350	350	125/250	250	20/30	27/37	36/53
BA 2VH	20	PP	2200	2870	2743	1743	1514	2442	2547	350	350	125/250	250	20/30	27/37	36/53
BA 2VH	20	PP	2300	3000	2791	1743	1514	2442	2547	350	350	125/250	250	20/30	27/37	36/53
BA 2VH	20	GP	1700	3000	2639	1903	1549	2699	2866	459	350	125/250	250	20/30	27/37	36/53
BA 2VH	20	GP	1800	3150	2687	1903	1549	2699	2866	459	350	125/250	250	20/30	27/37	36/53
BA 2VH	20	GP	1900	3300	2735	1903	1549	2699	2866	459	350	125/250	250	20/30	27/37	36/53
BA 2VH	20	GP	2000	3500	2785	1903	1549	2699	2866	459	350	125/250	250	20/30	27/37	36/53
BA 2VH	20	GP	2100	3650	2833	1903	1549	2699	2866	459	350	125/250	250	20/30	27/37	36/53
BA 2VH	20	GP	2200	3830	2882	1903	1549	2699	2866	459	350	125/250	250	20/30	27/37	36/53
BA 2VH	20	GP	2300	4000	2930	1903	1549	2699	2866	459	350	125/250	250	20/30	27/37	36/53
BA 2VH	25	PP	1700	3000	2709	1921	1567	2699	2866	459	350	125/250	250	24/36	38/53	54/70
BA 2VH	25	PP	1800	3150	2760	1921	1567	2699	2866	459	350	125/250	250	24/36	38/53	54/70
BA 2VH	25	PP	1900	3300	2811	1921	1567	2699	2866	459	350	125/250	250	24/36	38/53	54/70
BA 2VH	25	PP	2000	3500	2861	1921	1567	2699	2866	459	350	125/250	250	24/36	38/53	54/70
BA 2VH	25	PP	2100	3650	2911	1921	1567	2699	2866	459	350	125/250	250	24/36	38/53	54/70
BA 2VH	25	PP	2200	3830	2962	1921	1567	2699	2866	459	350	125/250	250	24/36	38/53	54/70
BA 2VH	25	PP	2300	4000	3013	1921	1567	2699	2866	459	350	125/250	250	24/36	38/53	54/70
BA 2VH	25	GP	1700	3670	2837	2061	1597	2955	3147	557	350	125/250	250	24/36	38/53	54/70
BA 2VH	25	GP	1800	3900	2891	2061	1597	2955	3147	557	350	125/250	250	24/36	38/53	54/70
BA 2VH	25	GP	1900	4100	2944	2061	1597	2955	3147	557	350	125/250	250	24/36	38/53	54/70
BA 2VH	25	GP	2000	4330	2998	2061	1597	2955	3147	557	350	125/250	250	24/36	38/53	54/70
BA 2VH	25	GP	2100	4550	3052	2061	1597	2955	3147	557	350	125/250	250	24/36	38/53	54/70
BA 2VH	25	GP	2200	4770	3106	2061	1597	2955	3147	557	350	125/250	250	24/36	38/53	54/70
BA 2VH	25	GP	2300	5000	3160	2061	1597	2955	3147	557	350	125/250	250	24/36	38/53	54/70

GP : large size - PP : small size  
Kg : Weight without suspension link