

- 1 Unión cardan macho.
- 2 Motor de giro 360°.
- 3 Superestructura de acero HLE.
- 4 2 cilindros verticales.
- 5 Ejes tratados HF.
- 6 Cucharras de acero anti-desgaste. 2 perfiles de cucharras según capacidad.
- 7 Dientes o contra cuchillas reversibles.
- 8 Cuchillas opcionales.



Perfil



A

B

C

D



	t	Perfil	L	mm	lt	kg	A	B	C	D	bar	l/mn	bar	l/mn	t
BA 702 T	25	PP	1500	2540	2830	3176	2288	2454	3032	350	150/200	250	24/36	39/53	
BA 702 T	25	PP	1600	2710	2890	3176	2288	2454	3032	350	150/200	250	24/36	39/53	
BA 702 T	25	PP	1700	2900	2950	3176	2288	2454	3032	350	150/200	250	24/36	39/53	
BA 702 R	25	PP	1500	2540	2830	3090	2060	2454	2860	350	150/200	250	24/36	39/53	
BA 702 R	25	PP	1600	2710	2890	3090	2060	2454	2860	350	150/200	250	24/36	39/53	
BA 702 R	25	PP	1700	2900	2950	3090	2060	2454	2860	350	150/200	250	24/36	39/53	
BA 702 R	25	PP	1800	3060	3005	3090	2060	2454	2860	350	150/200	250	24/36	39/53	
BA 702 R	25	PP	1900	3240	3060	3090	2060	2454	2860	350	150/200	250	24/36	39/53	
BA 702 R	25	PP	2000	3410	3120	3090	2060	2454	2860	350	150/200	250	24/36	39/53	
BA 702 R	25	PP	2100	3590	3180	3090	2060	2454	2860	350	150/200	250	24/36	39/53	
BA 702 R	25	PP	2200	3760	3240	3090	2060	2454	2860	350	150/200	250	24/36	39/53	
BA 702 R	25	PP	2300	3930	3295	3090	2060	2454	2860	350	150/200	250	24/36	39/53	
BA 702 R	25	PP	2400	4110	3350	3090	2060	2454	2860	350	150/200	250	24/36	39/53	
BA 702 R	25	PP	2500	4280	3410	3090	2060	2454	2860	350	150/200	250	24/36	39/53	
BA 702 R	25	GP	1500	2980	2905	3180	2060	2630	3050	350	150/200	250	24/36	39/53	
BA 702 R	25	GP	1600	3180	2965	3180	2060	2630	3050	350	150/200	250	24/36	39/53	
BA 702 R	25	GP	1700	3390	3025	3180	2060	2630	3050	350	150/200	250	24/36	39/53	
BA 702 R	25	GP	1800	3590	3085	3180	2060	2630	3050	350	150/200	250	24/36	39/53	
BA 702 R	25	GP	1900	3800	3145	3180	2060	2630	3050	350	150/200	250	24/36	39/53	
BA 702 R	25	GP	2000	4000	3200	3180	2060	2630	3050	350	150/200	250	24/36	39/53	
BA 702 R	25	GP	2100	4200	3260	3180	2060	2630	3050	350	150/200	250	24/36	39/53	
BA 702 R	25	GP	2200	4400	3320	3180	2060	2630	3050	350	150/200	250	24/36	39/53	
BA 702 R	25	GP	2300	4610	3380	3180	2060	2630	3050	350	150/200	250	24/36	39/53	
BA 702 R	25	GP	2400	4815	3440	3180	2060	2630	3050	350	150/200	250	24/36	39/53	
BA 702 R	25	GP	2500	5020	3500	3180	2060	2630	3050	350	150/200	250	24/36	39/53	

GP : Perfil grande – Perfil pequeño
Kg : peso sin cardan

BA 702

