

GENERAL-PURPOSE BUCKET



Robustness and safety for general purpose buckets.

General purpose bucket (UG) models are designed to work with excavators from 1.1 to 27 tons.

They are designed for earthmoving in soft materials such as soil. They are fitted with standard Arden Equipment teeth.



Standard profile

Arden Equipment offers a standard profile designed for earthmoving and loading operations.

Characteristics

- ✓ Compatible with QA / UA / AECW / AES / AIO quick couplers, Tilt and Tiltrotator systems, or direct mounting.
- ✓ Optimal penetration and bucket filling.
- ✓ Maintains the OEM linkage kinematics depending on the coupler.
- ✓ Buckets up to R40 fitted with lifting hooks (on the wear strips or on the couplers).
- ✓ Bucket stability on the ground.
- ✓ Supplied with Arden teeth as standard. Other tooth systems available on request.
- ✓ Reversible on most models (for QA and AECW, please contact us).

Options :

Plain cutting edge
Welded arrow wear strip

Other options: please contact us.

Safety

Versatility

Compatibility

Robustness



Technical drawings

Image of an R05G - R10G




Image of an R20G - R25G




Image of an R30G - R40G





Image of an R50G



t	Reference	KG *		A	B	Width / capacity	
		min	max			min	max
		Kg	Kg			mm/lt	mm/lt
1.1 - 1.4	R05G05	29	37	272	347	205/11	400/24
1.5 - 2	R05G11	33	61	375	420	205/20	600/65
2.1 - 3	R05G31	38	68	480	468	205/25	600/90
3.1 - 3.5	R05G42	61	118	584	647	300/65	800/200
2.6 - 3	R10G12	52	99	442	488	250/35	700/115
3.1 - 4.9	R10G22	71	128	584	647	300/65	800/200
5 - 6	R10G32	81	140	655	697	300/75	800/240
6 - 8**	R20G12	118	232	684	805	300/90	1000/360
8 - 10	R20G22	129	246	791	883	300/110	1000/450
10 - 11	R25G22	173	312	791	883	400/150	1100/505
12 - 16	R30G32	319	513	883	1067	450/260	1200/830
16 - 20	R40G32	406	664	965	1208	500/350	1300/1050
20 - 25	R50G22	661	961	937	1223	600/460	1300/1080
25 - 27	R50G42	709	1141	1072	1297	600/550	1500/1560

* Weight with QA and Arden teeth

** 7.5 t maximum for loaders

Some models with narrow widths can be supplied with parallel side plates: please contact us.

Technical data and visuals are non-contractual and subject to change without prior notice.



+33 (0)3 24 33 64 30

contact@arden-equipment.com

9 avenue de l'Industrie FR - 08000 Charleville-Mézières

www.arden-equipment.com

