

RAKE BUCKET



Adaptable to your material-handling operations

Rake buckets are designed to work with excavators from 1.5 to 27 tons.

With their spaced bars, they excel in numerous applications:

- Ground-cleaning and soil-preparation tasks such as brush clearing, uprooting, and lawn scarification prior to replanting.
- Maintenance and cleaning of water-filled ditches, as well as pond cleaning.
- Vineyard removal.





Characteristics

- ✓ Compatibility with QA / UA / AECW / AES / AIO quick couplers, AT and ATR systems, or direct mount
- ✓ Optimal penetration
- ✓ Respect of the original OEM kinematics depending on the coupler system
- ✓ Reversible on most models (contact us)

Options

- ✓ Different widths
- ✓ Different bar spacing / pitches. Available on request



	Reference	L	A	 *
t		mm	mm	Kg
1,5 - 3,5	R05W11	1200	78	103
2,6 - 6	R10W12	1200	100	176
6 - 12	R20W22	1500	190	355
12 - 16	R30W31	Contact us		
16 - 20	R40W31	Contact us		
20 - 27	R50W41	Contact us		

* Data, including weight, is provided for information only and may vary depending on the configuration and excavator adaptations.

Technical data and visuals are non-contractual and subject to change without prior notice.

Printed by Fusion Graphic - 4 Rue François Urano, 08000 Warcq - Do not discard on public roads.



+33 (0)3 24 33 64 30
 contact@arden-equipment.com
 9 avenue de l'Industrie FR - 08000 Charleville-Mézières
 www.arden-equipment.com

